

YANTON®
PROFESSIONAL FM TRANSCEIVER

T-650

Professional FM Transceiver



FEATURES

- 10W/5W/2W Power Switch with Side-key operation •
- Wide/Narrow Bandwidth Selection 12.5KHz/25KHz •
- Priority Channel Scan •
- TOT function •
- DTMF/PTT ID •
- Remote Kill , Stun, Activate & Revive •
- High Li-on Battery Capacity 2800MAH •

YANTON® T-650
PROFESSIONAL FM TRANSCEIVER

HIGH POWER OUTPUT



FEATURES

- 10W/5W/2W Power Switch with Side-key operation •
- Wide/Narrow Bandwidth Selection 12.5KHz/25KHz •
- Priority Channel Scan •
- TOT function, DTMF/PTT ID •
- Remote Kill , Stun, Activate & Revive •
- High Li-on Battery Capacity 2800MAH •

SPECIFICATION

GENERAL

Frequency Range	VHF: 136-174MHz
	UHF: 400-480MHz / 450-520MHz
Operating Temperature	-25°C~+55°C
Frequency Spacing	25/12.5KHz
Frequency Stability	±2.5ppm
Channel Capacity	16 Group
Working voltage	7.4V
Battery capacity	2800mAh Li-ion battery
Antenna Impedance	50Ω
Dimension	112mm×60mm×40mm
Weight	232g (Include Antenna & Battery)

TRANSMITTER (ETSI EN 300 086 standard testing)

Output power	10W/5W
Modulation Mode	16KΦF3E / 8KΦF3E
Modulation Limited	±5KHz/±2.5KHz
Audio Distortion	≤5%
Residual frequency modulation	-45dB/-40dB
Adjacent Channel Power	-70dB/-60dB
Spurious and Harmonic Wave	-36dBm<1GHz -30dBm>1GHz

RECEIVER (ETSI EN 300 086 standard testing)

Receiving Sensitivity	≤0.18uV / 0.22uV
Adjacent Channels Selectivity	≥70dB/60dB
Intermediation	≥60dB
Spurious Response	≥70dB
SNR	≥50/45dB
Audio Output Power	1W
Audio Distortion	≤5%

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.